

Part No.

# QSCM-2MSA-20-2

QSCM manifold, 1/4" MNPT gauge adapter, 20ft, 2ft hoses, (2) 1/4" MNPT process conn., nylon bag

Attach a gauge or pressure calibrator directly to the calibration manifold and easily perform static pressure calibrations (pressure gauge not included)

## Features

- Fine adjustment piston provides precise pressure control instead of trying to make adjustments with a pressure regulator and a needle valve
- Soft-seated valves make filling and venting the system very precise
- Compact design allows the manifold, gauge adapter and hoses to fit in the included nylon bag
- Low volume Quick-test hose, gauge adapter and process connection reduce gas usage and make nitrogen cylinders last longer
- Each kit comes with the hoses and gauge or pressure calibrator adapter needed so that you can start calibrating within minutes
- Made in U.S.A.

## Item Includes

- Assembly - QSCM Assembly (QSCM)
- Gauge Adapter - 1/4" male NPT x female Quick-test, no check-valve, S.S. (QTHA-2MSA)
- Hose - Quick-test 6900 psi hose, S.S. hose ends, 20 ft (6.10 m) long (QSQS-HOS-20ft)
- Hose - Quick-test 6900 psi hose, S.S. hose ends, 2 ft (61 cm) long (QSQS-HOS-2ft)
- Hose Adapter - 1/4" male NPT x male Quick-test, no check-valve, S.S. (QTHA-2MS0)
- Hose Adapter - 1/4" male NPT x male Quick-test, no check-valve, S.S. (QTHA-2MS0)

## Specifications

|                   |   |
|-------------------|---|
| Pressure Range    | 0 to 5000 psi (0 to 345 bar)  |
| Temperature range | 0 to 130 °F (-18 to 54 °C)  |
| Construction      | Stainless Steel   |
| Seal materials    | Buna-N, Delrin, Teflon  |
| Weight            | 2.09 lb (0.9 kg)  |
| Dimensions        | H: 3.78 in (9.60 cm) x W: 5.16 in (13.11 cm) x D: 2.63 in (6.68 cm) |



QSCM-2MSA-20-2