

Part No.

QTCM-2MBA-20-2

QTCM manifold, 1/4" MNPT gauge adapter, 20ft, 2ft hoses, (2) 1/4" MNPT process conn., nylon bag

Attach a gauge or pressure calibrator directly to the calibration manifold and easily perform static pressure calibrations (pressure gauge not included)

Features

- Fine adjustment piston provides precise pressure control instead of trying to make adjustments with a pressure regulator and a needle valve
- Soft-seated valves make filling and venting the system very precise
- Compact design allows the manifold, gauge adapter and hoses to fit in the included nylon bag
- Low volume Quick-test hose, gauge adapter and process connection reduce gas usage and make nitrogen cylinders last longer
- Each kit comes with the hoses and gauge or pressure calibrator adapter needed so that you can start calibrating within minutes
- Made in U.S.A.

Item Includes

- Assembly - QTCM Assembly (QTCM)
- Gauge Adapter - 1/4" male NPT x female Quick-test, no check-valve, brass (QTHA-2MBA)
- Hose - Quick-test 6900 psi hose, brass hose ends, 20 ft (6.10 m) long (QTQT-HOS-20ft)
- Hose - Quick-test 6900 psi hose, brass hose ends, 2 ft (61 cm) long (QTQT-HOS-2ft)
- Hose Adapter - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MBO)
- Hose Adapter - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MBO)

Specifications

Pressure Range	0 to 3000 psi (0 to 207 bar)
Temperature range	0 to 130 °F (-18 to 54 °C)
Construction	Brass
Seal materials	Buna-N, Delrin, Teflon
Weight	2.17 lb (1.0 kg)
Dimensions	H: 3.78 in (9.60 cm) x W: 5.16 in (13.11 cm) x D: 2.63 in (6.68 cm)



QTCM-2MBA-20-2