



Part No.

# QTQT-HOS-1m

*Quick-test 6900 psi hose, brass hose ends, 1 m (3.3 ft) long*

Microbore hoses that provide a very quick, low volume, high pressure way of connecting to any pressure instrumentation, hand pump, calibration source or device under test

## Features

- Low volume reduces the pumping effort or compressed gas usage in pressure calibration
- No thread sealant required – connect adapters to without wrenches, thread sealant or thread tape
- Bubble tight connections to 6900 psi (475 bar) with no moving parts reduces maintenance to almost zero
- Hose is hard to break and very flexible
- Adapt from hose to virtually any device under test with only one connection
- Silver color dramatically reduces the effect that changing temperature has on pressure stability
- A corrosion resistant strain-relief on each hose end reduces wear and dramatically increases hose life
- Hose is pin-pricked for use in Natural Gas applications
- Made in U.S.A.

## Specifications

Length	1 m
Pressure Range	0 to 6900 psi (0 to 475 bar)
Burst Pressure	27000 psi (1,860 bar)
End 1	Female Quick-test, brass
End 2	Female Quick-test, brass
Temperature range	-40 to 140 °F (-40 to 60 °C)
Outer Diameter	0.2 in (5.1 mm)
Inner Diameter	0.08 in (2.0 mm)
Minimum Bend Radius	1 in (25.4 mm)
Color	Silver
Construction	Polyamide core tube, High tensile synthetic fiber and polyamide outer cover
End materials	Brass
Fluid Media	Water, Petroleum Based Oil, Air, Inert Gas