

Moisture, Fluid Trap (3000 psi / 210 bar)

Increases confidence and efficiency in pneumatic calibrations by eliminating unwanted fluid or moisture that can contaminate a pressure calibrator or Nitropak

Features:

- Quick-release lid allows for easy cleaning of dirt or liquid without tools
- Entraps fluid and debris out of system to prevent blocking or plugging
- High pressure trap is ideal for pneumatic systems
- Compatible with all Ralston Instruments Quick-test hoses and adapters
- Comes with either only Quick-test ports (for use with Nitropak) or with both Quick-test ports and NPT top and bottom connections
- Made in U.S.A.



Specifications	
Pressure range	3000 psi (210 bar)
Bottom port (stainless steel)	Female Quick-test (QTHA-3SSA-LD)
Top port (stainless steel)	Male Quick-test (QTHA-3SSA)
Material	Anodized aluminum, stainless steel
Seal material	Buna-N, Teflon™
Weight	1.2 lb (540 g)

Ordering information:	
TRSO trap with stainless steel NPT connections	
Model	Description
NPAK-TRSO	Trap with no top connection, no bottom connection
NPAK-TRSO-2MS0-2FSA	Trap with 1/4" female NPT (QTHA-2FSA) top connection, 1/4" male NPT (QTHA-2MS0) bottom connection

For accessories, repair kits and hoses see page 17. For a complete list of accessories and parts see product manual or detailed specification sheet. For a list of the most commonly used gauge and process connections see page 18. For a complete list refer to Ralston Instruments *Pressure Connection* catalog. Contact your Ralston Instruments dealer or the factory for information on reference gauges and pressure calibration kits.