

Part No.

# APGV-0000

*APGV (300 psi / 20 bar) pump, 1/4" female NPT gauge swivel, 3ft hose, 1/4" MNPT process conn.*

Quick and efficient pneumatic field testing of pressure transmitters, gauges or switches.



APGV-0000

## Included Items

- Hand Pump - APGV Assembly (APGV)
- Process Connection - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Hose - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)
- Gauge Swivel - 1/4" Female NPT swivel, brass (SWIV-2FBW)

## Specs/Attributes

Burst Pressure	27000 PSI
Color	Silver
Fine Adjustment Resolution	0.010 PSI
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Has Check Valve	No
Inner Diameter	0.08 In
Length	3 ft
Materials	Aluminum, Brass, Plated Steel, Stainless Steel
Max Pressure	300 PSI
Max Temperature	130 °F
Max Vacuum	0 In Hg
Media Compatibility	Air, Inert Gas, Natural Gas
Min Temperature	0 °F
Minimum Bend Radius	1 In
Outer Diameter	0.2 In
Outlet Port	Male Quick-test

## Specs/Attributes

Pressure Media	Air
Pressure Reference	None
Process Connection	1/4" Male NPT
Reference Connection	1/4" Female NPT
Seal Materials	Buna-N, Delrin, Teflon
Type	QT
Wrench Size	15, 19 mm 9/16, 3/4 In