

Part No.

# DPOV-0000

*DPOV (125 psi / 8.6 bar) pump, no gauge adapter, 3ft hose, 1/4" MNPT process connection*

The ideal solution for very precise low pressure calibration or differential pressure testing using an external pressure calibrator as the reference



DPOV-0000

## Included Items

- Hand Pump - DPOV Assembly (DPOV)
- Process Connection - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Hose - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)

## Specs/Attributes

Burst Pressure	27000 PSI
Color	Silver
Fine Adjustment Resolution	0.010 PSI
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Has Check Valve	No
Inner Diameter	0.08 In
Length	3 ft
Materials	Anodized Aluminum, Brass, Stainless Steel
Max Pressure	125 PSI
Max Temperature	130 °F
Max Vacuum	0 In Hg
Media Compatibility	Air, Inert Gas, Natural Gas
Min Temperature	0 °F
Minimum Bend Radius	1 In
Outer Diameter	0.2 In
Outlet Port	Male Quick-test, Male Quick-test with cap and chain
Pressure Media	Air
Pressure Reference	None
Process Connection	1/4" Male NPT
Reference Connection	None
Seal Materials	Buna-N, Delrin, Teflon
Type	QT

**Specs/Attributes**

Wrench Size	15 mm 9/16 In
-------------	------------------