

Part No.

DPOV-2FBA-VT

DPOV (125 psi / 8.6 bar) pump, 1/4" female NPT gauge adapter, 3ft hose, 1/4" MNPT process conn., Viton seals

Perform very precise low pressure calibration or differential pressure calibration using an attached gauge or calibrator (gauge and calibrator not included)



DPOV-2FBA-VT

Included Items

- Hand Pump - DPOV Pneumatic Hand Pump, Viton seals (DPOV-VT)
- Reference Connection - 1/4" female NPT x female Quick-test, no check-valve, brass (QTHA-2FBA)
- Process Connection - 1/4" male NPT x male Quick-test, no check-valve, brass, Viton seals (QTHA-2MB0-VT)
- Hose - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)

Specs/Attributes

Max Pressure	125 PSI / 8.6 bar / 860 kPa
Max Vacuum	0.00 InHg / 0.0 kPa
Materials	Anodized Aluminum, Brass, Stainless Steel
Seal Materials	Buna-N, Delrin, Teflon
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Hose 1	Quick-test Hose, Stainless Steel ends, 2ft / 0.6m long
Pressure Reference	None
Process Connection	1/4" Male NPT
Reference Connection	1/4" Female NPT
Country of origin	USA
Weight	1.61 lbs / 730 grams
Dimensions	H: 2.87 in (7.29 cm) x W: 7.93 in (20.14 cm) x D: 3.5 in (8.89 cm)

Hand Pump DPOV-VT

Hand Pump DPOV-VT

Max Pressure	125 PSI / 8.6 bar / 860 kPa
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Pressure Media	Air
Fine Adjustment Resolution	0.01 PSI / 0.07 mbar / 0.00 kPa
Media Compatibility	Air, Inert Gas, Natural Gas
Outlet Port	Male Quick-test, Male Quick-test with cap and chain
Materials	Anodized Aluminum, Brass
Seal Materials	Delrin, Viton
Country of origin	USA
Weight	1.60 lbs / 725 grams
Dimensions	H: 2.9 in (7.37 cm) x W: 8 in (20.32 cm) x D: 3.4 in (8.64 cm)

Reference Connection QTHA-2FBA

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Wrench Size	3/4 In 19 mm
Dimensions	H: 1.52 in (3.86 cm) x W: 0.75 in (1.91 cm)

Process Connection QTHA-2MB0-VT

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm)

Hose QTQT-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Inner Diameter	0.08 In / 3.00 mm
Length	3 ft / 92 cm
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT