

Part No.

# DPOV-KIT5-VJ

*DPOV pneumatic pump, 100 psi/700 kPa LC20 gauge, case, 3ft hose, 1/4" MNPT adapter, zippered bag*

Calibration kit with pump and LC20 digital pressure gauge



DPOV-KIT5-VJ

## Included Items

- Pressure Reference - LC20 pressure gauge, -15 to 100 psi / -100 to 700 kPa, 1/4" Male NPT bottom connection (LC20-VJ2M-00-00)
- Hand Pump - DPOV Pneumatic Hand Pump (DPOV)
- Case - DPOV, DV0V or DPPV Case (DPOV-CASE)
- Process Connection - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Hose - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)
- Reference Connection - 1/4" female NPT x female Quick-test, no check-valve, brass (QTHA-2FBA)
- Bag - Zippered bag to hold hose and adapters, nylon (SM-0084)

## Specs/Attributes

Weight	2.15 lbs / 975 grams
Dimensions	H: 8 in (20.32 cm) x W: 7.93 in (20.14 cm) x D: 2.9 in (7.37 cm)

## Pressure Reference LC20-VJ2M-00-00

Battery Count	2
Battery Life	1000 Hours
Battery Type	AA Alkaline (IEC-LR6)
Bluetooth Radio Installed	No
Calibration Certificate	ISO 17025:2017 Accredited
Certifications	Certified to CSA Standard C22.2 No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU

## Pressure Reference LC20-VJ2M-00-00

Country of origin	USA
Datalogging	PC based (via USB)
Electrical Rating	50 mA @ 5 VDC
Harmonized Code	9026.20.0000
Ingress Protection	IP67 (1 meter water submersion for 30 minutes)
LCD Display	2.4 in / 61 mm segmented LCD Display
Materials	ABS / Polycarbonate Blend, Powder Coated Aluminum
Max Operating Temperature	120 °F / 50 °C
Min Operating Temperature	-4 °F / -20 °C
Panel Mount	No
Primary Power	Battery Power
Process Connection Location	Bottom mount
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Temperature Compensation	None
USB Connection	USB (Micro B)
W1 Radio Installed	No
Wetted Materials	316 Stainless Steel
Wireless	None
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Weight	12.6 oz / 355 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)

## Hand Pump DP0V

Max Pressure	125 PSI / 8.6 bar / 860 kPa
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Burst Pressure	1000 PSI / 70 bar / 7.00 MPa
Media Compatibility	Air, Inert Gas, Natural Gas
Outlet Port	Male Quick-test, Male Quick-test with cap and chain
Fine Adjustment Resolution	0.01 psi / 70 Pa
Country of origin	USA
Harmonized Code	8414.20.0000
Materials	Anodized Aluminum, Brass
Seal Materials	Buna-N, Delrin

## Hand Pump DPOV

Piston Displacement	1.25 Cu In
Weight	1.60 lbs / 725 grams
Dimensions	H: 2.9 in (7.37 cm) x W: 8 in (20.32 cm) x D: 3.4 in (8.64 cm)

## Case DPOV-CASE

Ingress Protection	IP67 (1 meter water submersion for 30 minutes), MIL-STD-810F
Materials	ABS Plastic, Polyethylene foam
Impact Resistance	MIL-STD-3010C
Weight	6.00 lbs / 2.72 kg
Dimensions	H: 14.9 in (37.85 cm) x W: 12.1 in (30.73 cm) x D: 6.9 in (17.53 cm)

## Process Connection QTHA-2MB0

Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Country of origin	USA
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	1.09 oz / 31 grams
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)

## Hose QTQT-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	3ft / 0.91 m
Inner Diameter	0.08 In / 3.00 mm
Length	3 ft / 92 cm
Materials	Brass
Max Operating Temperature	140 °F / 60 °C

### Hose QTQT-HOS-3ft

Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	2.68 oz / 76 grams

### Reference Connection QTHA-2FBA

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Wrench Size	3/4 In 19 mm
Connector End 1	1/4" Female NPT (ASME B1.20.1)
Connector End 2	Female Quick-test
Weight	2.05 oz / 58 grams
Dimensions	H: 1.52 in (3.86 cm) x W: 0.75 in (1.91 cm) x D: 0.75 in (1.91 cm)

### Bag SM-0084

Materials	Zippered Nylon
Country of origin	USA
Weight	3 oz / 85 grams
Dimensions	H: 6.5 in (16.51 cm) x W: 6.5 in (16.51 cm) x D: 0.5 in (1.27 cm)