

Part No.

HPGV-0000

3000 psi (210 bar) HPGV Hydraulic pump, 1/4" female NPT gauge swivel, 3ft hose, 1/4" MNPT process connection

An excellent pump to be used with a digital pressure gauge



HPGV-0000

Included Items

- Hand Pump - HPGV Assembly (HPGV)
- Process Connection - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Hose - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)
- Gauge Swivel - 1/4" Female NPT swivel, brass (SWIV-2FBW)

Specs/Attributes

Burst Pressure	27000 PSI
Color	Silver
Fine Adjustment Resolution	.01 PSI
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Has Check Valve	No
Hose 1	Quick-test Hose, Brass ends, 3ft / 0.9m long
Inner Diameter	0.08 In
Length	3 ft
Materials	Anodized Aluminum, Brass, Plated Steel
Max Pressure	3000 PSI
Max Temperature	130 °F
Max Vacuum	In Hg
Media Compatibility	Petroleum Based Oil, Water
Min Temperature	0 °F
Minimum Bend Radius	1 In
Outer Diameter	0.2 In

Specs/Attributes

Outlet Port	Male Quick-test with check-valve
Pressure Reference	None
Process Connection	1/4" Male NPT
Reference Connection	1/4" Female NPT
Seal Materials	Buna-N, Delrin, Synthetic Cork, Teflon
Type	QT
Wrench Size	9/16, 3/4 In 15, 19 mm