

Part No.

 **LC-GA2M**

LC-GA2M

LC vacuum, 30Hg / 780 mmHg, 1/4" Male NPT connection

Specs/Attributes

Accuracy - Pressure Measurement	+/- 0.25% of Full Scale (ASME B40.100 Grade 3A/ISO Class 0.25)
Burst Pressure	20 PSI / 1.4 bar / 140 kPa
Country of origin	USA
Engineering Units	atm, bar, cmH2O @4°C, cmHg @ 0°C, ftH2O @39°F, inHg @39°F, kgf / cm^2, kPa, mbar, mmH2O @4°C, mmHg @0°C, oz / in^2, psi, Torr
Max Operating Temperature	120 °F / 50 °C
Max Pressure	0.00 PSI / 0.00 mbar / 0.00 kPa
Max Storage Temperature	165 °F / 75 °C
Max Vacuum	-30.00 InHg / -101.6 kPa
Measurement Type	Gauge Vacuum
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Light motor oil, Mineral Oil, Natural Gas, Petroleum Based Oil, Ralston Calibration Oil, Skydrol, Transmission fluid, Water, Windshield washer fluid, Oxygen (If Oxygen cleaned)
Min Operating Temperature	-4 °F / -20 °C
Min Storage Temperature	-40 °F / -40 °C
Process Connection	1/4" Male NPT
Resolution	0.00001 atm
Sensor Type	Pressure Sensor
Wetted Materials	316 Stainless Steel
Wrench Size	7/8 In 23 mm