

Part No.

LC10-VF2M

LC10 pressure gauge, -15 to 30 psi / -100 to 200 kPa, 1/4" Male NPT bottom connection

The LC10 is a robust device that measures and displays pressure readings on a large, backlit screen. The LC10 has the ability to show High and Low pressure values on-screen, change between 15 different engineering units or add custom engineering units. The included PC FieldLab Desktop software can be used for calibration, testing and live viewing of pressure.



LC10-VF2M

Specs/Attributes

Battery Count	2
Battery Life	1500 Hours
Battery Type	AA Alkaline (IEC-LR6)
Calibration Certificate	Not included
Certifications	Certified to CSA Standard C22.2 No. 61010-1, Conforms to UL / IEC / EN / AS Standard No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU
Country of origin	USA
Datalogging	PC based (via USB)
Electrical Rating	50 mA @ 5 VDC
Harmonized Code	9026.20.0000
Ingress Protection	IP67 (1 meter water submersion for 30 minutes)
LCD Display	2.4 in / 61 mm segmented LCD Display
Materials	ABS / Polycarbonate Blend, Powder Coated Aluminum
Max Operating Temperature	120 °F / 50 °C
Min Operating Temperature	-4 °F / -20 °C
Operating Altitude (max)	10,000 ft (3050 m)
Panel Mount	No
Primary Power	Battery Power
Process Connection Location	Bottom mount
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)

Specs/Attributes

Relative Humidity	0% to 90% (-10 to 35 °C) , 0% to 70% (35 to 50 °C)
Sensor Type	High Precision MEMS
Temperature Compensation	None
USB Connection	USB (Micro B)
Wetted Materials	316 Stainless Steel
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Weight	12.6 oz / 355 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 3.1 in (7.87 cm)

Sensor A (Bottom)

Accuracy - Pressure Measurement	+/- 0.25% of Full Scale (ASME B40.100 Grade 3A/ISO Class 0.25)
Engineering Units	atm, bar, cmH2O @4 °C, inH2O @39 °C, kPa, mbar, psi, inHg @39 °F, kgf / cm^2, mmHg @0 °C, Torr, mmH2O @4 °C, ftH2O @39 °F, cmHg @ 0 °C, oz / in^2
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water
Country of origin	USA
Max Operating Temperature	120 °F / 50 °C
Wrench Size	7/8 In 23 mm
Measurement Type	Gauge Pressure
Max Pressure	30 PSI / 2 bar / 200 kPa
Max Vacuum	30 InHg / 101.6 kPa
Sensor Type	Pressure Sensor
Min Storage Temperature	-40 °F / -40 °C
Process Connection	1/4" Male NPT
Min Operating Temperature	-4 °F / -20 °C
Wetted Materials	316 Stainless Steel
Max Storage Temperature	165 °F / 75 °C
Burst Pressure	120 PSI / 8.3 bar / 830 kPa