

Part No.

LC20-GA2M-00-00

LC20 Vacuum gauge, 30Hg / 780 mmHg, 1/4" Male NPT bottom connection

The LC20 is a robust device that measures and displays pressure readings on a large, backlit screen. The LC20 has the ability to show High and Low pressure values on-screen, change between 15 different engineering units or add custom engineering units. The included PC FieldLab Desktop software can be used for calibration, testing and live viewing of pressure.



LC20-GA2M-00-00

Specs/Attributes

Battery Count	2
Battery Life	1000 Hours
Battery Type	AA Alkaline (IEC-LR6)
Burst Pressure	5 PSI / 34 mbar / 30 kPa
Calibration Certificate	NIST traceable (included)
Certifications	Certified to CSA Standard C22.2 No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU
Country of origin	USA
Datalogging	PC based (via USB)
Electrical Rating	50 mA @ 5 VDC
Engineering Units	atm, bar, cmH2O @4°C, inH2O @39°C, kPa, mbar, psi, inHg @39°F, kgf / cm ² , mmHg @0°C, ftH2O @39°F, cmHg @ 0°C, oz / in ²
Harmonized Code	9026.20.0000
Ingress Protection	IP67 (1 meter water submersion for 30 minutes)
LCD Display	2.4 in / 61 mm segmented LCD Display
Materials	ABS / Polycarbonate Blend, Powder Coated Aluminum
Max Operating Temperature	120 °F / 50 °C
Max Storage Temperature	165 °F / 75 °C
Max Vacuum	30 InHg / 101.6 kPa
Measurement Type	Gauge Vacuum
Media Compatibility	Inert Gas, Natural Gas, Petroleum Based Oil, Water, Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Mineral Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil

Specs/Attributes

Min Operating Temperature	-4 °F / -20 °C
Min Storage Temperature	-40 °F / -40 °C
Panel Mount	No
Pressure Measurement Uncertainty	+/- 0.1% of Full Scale (ASME B40.100 Grade 4A/ISO Class 0.1)
Primary Power	Battery Power
Process Connection	1/4" Male NPT (ASME B1.20.1)
Process Connection Location	Bottom mount
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Sensor Type	Pressure Sensor
Temperature Compensation	None
USB Connection	USB (Micro B)
W1 Radio Installed	No
Wetted Materials	316 Stainless Steel
Wrench Size	7/8 In 23 mm
Weight	12.6 oz / 355 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)