


Part No.



LC20

LC20 assembly without pressure or temperature sensor

Specs/Attributes

Panel Mount	No
Primary Power	Battery Power
Wireless	None
Harmonized Code	9026.20.0000
Calibration Certificate	ISO 17025:2017 Accredited
Electrical Rating	50 mA @ 5 VDC
Battery Type	AA Alkaline (IEC-LR6)
Data Logging	PC based (via USB)
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Temperature Compensation	None
Battery Count	2
Battery Life	1000 Hours
Certifications	Certified to CSA Standard C22.2 No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU
Ingress Protection	IP67 (1 meter water submersion for 30 minutes)
LCD Display	2.4 in / 61 mm segmented LCD Display
Materials	ABS / Polycarbonate Blend, Powder Coated Aluminum
Wetted Materials	316 Stainless Steel
Max Operating Temperature	120 °F / 50 °C
Min Operating Temperature	-4 °F / -20 °C
USB Connection	USB (Micro B)
Country of origin	USA
Weight	1.66 lbs / 755 grams
Dimensions	H: 1.8 in (4.57 cm) x W: 3.4 in (8.64 cm) x D: 4.2 in (10.67 cm)