Part No.

LC30-GY2H-TX125-B1

LC30 pressure / temperature gauge, 20000 psi back, M12 External Probe connection back, Bluetooth radio

The LC30 is a robust device that measures and displays pressure readings on a large, backlighted screen. It is AC powered with a battery backup. The LC30 has the ability to show High and Low pressure values on-screen, change between 15 different engineering units or add custom engineering units. The included PC FieldLab Desktop software can be used for calibration, testing and logging pressure.

LC30-GY2H-TX125-B1

Specs/Attributes

Backup Power	AAA Alkaline (IEC-LR03)
Battery Count	2
Battery Life	1000 Hours
Bluetooth Radio Installed	Yes
Calibration Certificate	ISO 17025:2017 Accredited
Certifications	Certified to CSA Standard C22.2 No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU
Contains Wireless Module	Yes
Country of origin	USA
Data Logging	PC based (via USB)
Electrical Rating	50 mA @ 5 VDC
Harmonized Code	9026.20.0000
Ingress Protection	IP67 (1 meter water submersion for 30 minutes)
LCD Display	2.4 in / 61 mm segmented LCD Display
Materials	ABS / Polycarbonate Blend, Powder Coated Aluminum
Max Operating Temperature	120 °F / 50 °C
Media Compatibility	Inert Gas, Natural Gas, Petroleum Based Oil, Water

Specs/Attributes

Min Operating Temperature	-4 °F / -20 °C
Operating Altitude (max)	10,000 ft (3050 m)
Panel Mount	Yes
Power Input	90-264 VAC, 50-60 Hz
Primary Power	AC Mains Power
Process Connection Location	Back mount
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Radio Approvals	FCC ID 2AA9B04, IC ID 12208A-04, Japan ID 210-107153, Korea - Clause 3, Article 58-2 of Radio Waves Act
Radio Type	Bluetooth 5 LE
Relative Humidity	0% to 90% (-10 to 35°C) , 0% to 70% (35 to 50°C)
Temperature Compensation	None
USB Connection	USB (Micro B)
W1 Radio Installed	Yes
Wetted Materials	316 Stainless Steel
Wireless	Bluetooth
Wireless Range	330 ft / 100 m
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	9/16-18 (1/4" HF4) Female High Pressure
Weight	12.6 oz / 355 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)

Sensor A (Back)

Burst Pressure	80000 PSI / 5515 bar / 550 MPa
Max Operating Temperature	120 °F / 50 °C
Min Operating Temperature	-4 °F / -20 °C
Wrench Size	7/8 In 23 mm
Measurement Type	Gauge Pressure
Max Pressure	20000 PSI / 1380 bar / 140 MPa
Wetted Materials	17-4 Stainless Steel
Engineering Units	atm, bar, cmHg @ 0°C, ftH2O @39°F, inHg @39°F, kgf / cm^2, MPa, psi
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Light motor oil, Mineral Oil, Natural Gas, Petroleum Based Oil, Ralston Calibration Oil, Skydrol, Transmission fluid, Water, Windshield washer fluid
Max Storage Temperature	165 °F / 75 °C

Sensor A (Back)

Min Storage Temperature	-40 °F / -40 °C
Sensor Type	Pressure Sensor
Materials	Stainless Steel
Process Connection	9/16-18 Female High Pressure (1/"4 HP)
Accuracy - Pressure Measurement	+/- 0.1% of Full Scale (ASME B40.100 Grade 4A/ISO Class 0.1)
Max Vacuum	0.00 InHg / 0.0 kPa
Country of origin	USA

Sensor B (Back)

Max Probe Temperature	300 °F / 150 °C
Min Probe Temperature	-22 °F / -30 °C
Thermal Probe	1/4 in / 6.35 mm diameter, 12 in / 30.5 cm long, external cable, 20 ft / 6.1 m long
Wetted Materials	316 Stainless Steel
Measurement Type	Temperature
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Accuracy - Temperature Measurement	+/- (0.15 +0.002*|t|)°C (IEC 60751 Class A)
Country of origin	USA
Electrical Connection	M12 female, A Code, Silicone seal, IP67
Temperature Units	°C, °F, K, R