

Part No.

NPAK-0000-0-0

Nitropak only, no gauge adapter, no hoses, no process connections

Self contained unit provides a precise nitrogen source for calibrating differential and static pressure instrumentation using an external pressure calibrator



NPAK-0000-0-0

Included Items

- Source - NPAK Assembly (NPAK)

Specs/Attributes

Cylinder Capacity	15.20 Sq Ft
Fill Vent Valves	soft seated construction
Fine Adjustment Resolution	.0005 PSI
Inlet Port	Male Quick-test with cap and chain
Internal Connections	1/8 in tubing (316 stainless steel)
Materials	ABS Plastic, Aluminum, Anodized Aluminum, Brass, Plated Steel, Stainless Steel, Zippered Nylon with Velcro
Max Pressure	3000 PSI
Max Temperature	130 °F
Max Vacuum	10 In Hg
Mechanical Rotation	42 turns (pressure balanced)
Media Compatibility	Air, Inert Gas, Natural Gas
Min Temperature	0 °F
Outlet Port	Male Quick-test with cap and chain
Overpressure Relief	3300 PSI
Pressure Media	Nitrogen, inert gas
Pressure Reference	Digital pressure gauge, 1000 PSIG Pressure
Seal Materials	Buna-N, Delrin, Teflon