

Part No.

NPAK-SS-VT

Nitropak Portable Nitrogen Source, Stainless, Viton

Nitropak Portable Nitrogen Source base unit without hoses or adapters with stainless or aluminum wetted components and viton seals.



NPAK-SS-VT

Specs/Attributes

Inlet Port	Male Quick-test with cap and chain
Media Compatibility	Air, Inert Gas, Natural Gas
Max Operating Temperature	140 °F / 60 °C
Fill Vent Valves	soft seated construction
Cylinder Capacity (water)	122 Cu In
Cylinder Capacity (compressed gas)	15.20 Cu Ft
Mechanical Rotation	42 turns (pressure balanced)
Max Pressure	3000 PSI / 200 bar / 20 MPa
Fine Adjustment Resolution	0.0005 psi / 3 Pa
Materials	Anodized Aluminum, Delrin, Powder Coated Steel, Stainless Steel, Zippered Nylon with Velcro
Outlet Port	Male Quick-test with cap and chain
Seal Materials	Delrin, Teflon, Viton
Harmonized Code	9032.81.0060
Max Vacuum	10 InHg / 33.9 kPa
Overpressure Relief	3300 PSI / 230 bar / 23 MPa
Min Operating Temperature	0 °F / -18 °C

Specs/Attributes

Country of origin	USA
Internal Connections	1/8 in tubing (316 stainless steel)
Weight	29 lbs / 13 kg
Dimensions	H: 14.6 in (37.08 cm) x W: 18.5 in (46.99 cm) x D: 7.8 in (19.81 cm)