

Part No.

# NPAK-TRS0-2MS0-2MSA

*NPAK fluid trap (3000 psi, 210 bar), (1) 1/4" MNPT top conn., (1) 1/4" MNPT adapter bottom con, S.S.*

NPAK fluid trap (3000 psi, 210 bar), (1) 1/4" MNPT top conn., (1) 1/4" MNPT adapter bottom con, S.S.



NPAK-TRS0-2MS0-2MSA

## Included Items

- Fluid Trap - Fluid and Moisture Trap (TRAP)
- Top Connection - 1/4" male NPT x female Quick-test, no check-valve, S.S. (QTHA-2MSA)
- Bottom Connection - Female Quick-test outlet port with drain tube (for NPAK-TRS0), S.S. (QTHA-3SSA-LD)
- Process Connection - 1/4" male NPT x male Quick-test, no check-valve, S.S. (QTHA-2MS0)

## Specs/Attributes

|                   |                             |
|-------------------|-----------------------------|
| Country of origin | USA                         |
| Max Pressure      | 3000 PSI / 200 bar / 20 MPa |
| Max Vacuum        | 23 InHg / 77.9 kPa          |

## Specs/Attributes

|                           |                                                              |
|---------------------------|--------------------------------------------------------------|
| Materials                 | Anodized Aluminum, Stainless Steel                           |
| Seal Materials            | Buna-N, Teflon                                               |
| Min Operating Temperature | 0 °F / -18 °C                                                |
| Max Operating Temperature | 130 °F / 54 °C                                               |
| Weight                    | 1.30 lbs / 590 grams                                         |
| Dimensions                | H: 5.5 in (13.97 cm) x W: 2 in (5.08 cm) x D: 2 in (5.08 cm) |

## Fluid Trap TRAP

|                           |                                                                  |
|---------------------------|------------------------------------------------------------------|
| Max Pressure              | 3000 PSI / 200 bar / 20 MPa                                      |
| Max Vacuum                | 23 InHg / 77.9 kPa                                               |
| Min Operating Temperature | 0 °F / -18 °C                                                    |
| Max Operating Temperature | 130 °F / 54 °C                                                   |
| Country of origin         | USA                                                              |
| Dimensions                | H: 2.2 in (5.59 cm) x W: 2.2 in (5.59 cm) x D: 5.5 in (13.97 cm) |

## Top Connection QTHA-2MSA

|                           |                                                                  |
|---------------------------|------------------------------------------------------------------|
| Country of origin         | USA                                                              |
| Has Check Valve           | No                                                               |
| Materials                 | Stainless Steel                                                  |
| Max Operating Temperature | 225 °F / 105 °C                                                  |
| Max Pressure              | 5000 PSI / 350 bar / 35 MPa                                      |
| Max Vacuum                | 0.00 InHg / 0.0 kPa                                              |
| Wrench Size               | 9/16 In<br>15 mm                                                 |
| Connector End 1           | 1/4" Male NPT (ASME B1.20.1)                                     |
| Connector End 2           | Female Quick-test                                                |
| Weight                    | 1.54 oz / 44 grams                                               |
| Dimensions                | H: 1.68 in (4.27 cm) x W: 0.7 in (1.78 cm) x D: 0.7 in (1.78 cm) |

## Bottom Connection QTHA-3SSA-LD

|                   |                                                                   |
|-------------------|-------------------------------------------------------------------|
| Materials         | Stainless Steel                                                   |
| Seal Materials    | Buna-N                                                            |
| Country of origin | USA                                                               |
| Weight            | 0.9 oz / 26 grams                                                 |
| Dimensions        | H: 3.1 in (7.87 cm) x W: 0.62 in (1.57 cm) x D: 0.62 in (1.57 cm) |

**Process Connection** QTHA-2MS0

|                           |                                                                    |
|---------------------------|--------------------------------------------------------------------|
| Country of origin         | USA                                                                |
| Has Check Valve           | No                                                                 |
| Materials                 | Stainless Steel                                                    |
| Max Operating Temperature | 225 °F / 105 °C                                                    |
| Max Pressure              | 5000 PSI / 350 bar / 35 MPa                                        |
| Max Vacuum                | 0.00 InHg / 0.0 kPa                                                |
| Min Operating Temperature | 0 °F / -18 °C                                                      |
| Seal Materials            | Buna-N                                                             |
| Wrench Size               | 9/16 In<br>15 mm                                                   |
| Connector End 1           | 1/4" Male NPT (ASME B1.20.1)                                       |
| Connector End 2           | Male Quick-test                                                    |
| Weight                    | 1.01 oz / 29 grams                                                 |
| Dimensions                | H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm) |