

Part No.

NPAK-TRSO

Liquid trap with male Quick-test top port, female Quick-test bottom port

Eliminates unwanted fluid or moisture that can contaminate any gas system.



NPAK-TRSO

Included Items

- Fluid Trap - Fluid and Moisture Trap (TRAP)
- Top Connection - Male Quick-test outlet port, S.S. (QTHA-3SS0)
- Bottom Connection - Female Quick-test outlet port with drain tube (for NPAK-TRSO), S.S. (QTHA-3SSA-LD)

Specs/Attributes

Country of origin	USA
Max Pressure	3000 PSI / 200 bar / 20 MPa
Max Vacuum	23 InHg / 77.9 kPa
Materials	Anodized Aluminum, Stainless Steel
Seal Materials	Buna-N, Teflon
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Weight	1.14 lbs / 515 grams
Dimensions	H: 5.5 in (13.97 cm) x W: 2 in (5.08 cm) x D: 2 in (5.08 cm)

Fluid Trap TRAP

Max Pressure	3000 PSI / 200 bar / 20 MPa
Max Vacuum	23 InHg / 77.9 kPa
Min Operating Temperature	0 °F / -18 °C

Fluid Trap TRAP

Max Operating Temperature	130 °F / 54 °C
Country of origin	USA
Dimensions	H: 2.2 in (5.59 cm) x W: 2.2 in (5.59 cm) x D: 5.5 in (13.97 cm)

Top Connection QTHA-3SS0

Country of origin	USA
Materials	Stainless Steel
Max Pressure	5000 PSI / 350 bar / 35 MPa
Seal Materials	Buna-N
Wrench Size	9/16 In
Connector End 1	3/8-24 Male SAE/MS
Connector End 2	Male Quick-test
Weight	0.77 oz / 22 grams
Dimensions	H: 1.14 in (2.9 cm) x W: 0.64 in (1.63 cm) x D: 0.64 in (1.63 cm)

Bottom Connection QTHA-3SSA-LD

Materials	Stainless Steel
Seal Materials	Buna-N
Country of origin	USA
Weight	0.9 oz / 26 grams
Dimensions	H: 3.1 in (7.87 cm) x W: 0.62 in (1.57 cm) x D: 0.62 in (1.57 cm)