

Part No.

 **QSCM-2MSA-6m-1m**

QSCM-2MSA-6m-1m

QSCM manifold, fine adjust, 1/4" male NPT gauge conn., (1) 6 meter hose, (1) 1meter hose

Attach a gauge or pressure calibrator directly to the calibration manifold and easily perform static pressure calibrations (pressure gauge not included)

Included Items

- Manifold - QSCM Stainless Steel Calibration Manifold (QSCM)
- Reference Connection - 1/4" male NPT x female Quick-test, no check-valve, S.S. (QTHA-2MSA)
- Process Connection (Qty 2) - 1/4" male NPT x male Quick-test, no check-valve, S.S. (QTHA-2MS0)
- Hose 1 - Quick-test 6900 psi hose, SS hose ends, 6 m (19.7 ft) long (QSQS-HOS-6m)
- Hose 2 - Quick-test 6900 psi hose, S.S. hose ends, 1 m (3.3 ft) long (QSQS-HOS-1m)
- Bag - Zippered bag to hold hose and adapters, nylon (SM-0027)

Specs/Attributes

Materials	Anodized Aluminum, Stainless Steel
Seal Materials	Buna-N, Delrin, Teflon
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Hose 1	Quick-test Hose, Stainless Steel ends, 6m long
Hose 2	Quick-test Hose, Stainless Steel ends, 1m long
Pressure Reference	None
Process Connection	1/4" Male NPT
Reference Connection	1/4" Male NPT
Country of origin	USA
Weight	2.19 lbs / 995 grams
Dimensions	H: 3.78 in (9.6 cm) x W: 5.16 in (13.11 cm) x D: 2.63 in (6.68 cm)

Manifold QSCM

Inlet Port	Male Quick-test
Media Compatibility	Air, Inert Gas, Natural Gas
Outlet Port	Male Quick-test
Seal Materials	Buna-N, Delrin, Teflon

Manifold QSCM

Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Materials	Anodized Aluminum, Stainless Steel
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Fine Adjustment Resolution	0.1 psi / 690 Pa
Country of origin	USA
Harmonized Code	9032.81.0060
Weight	2.20 lbs / 1000 grams
Dimensions	H: 3.8 in (9.65 cm) x W: 5.1 in (12.95 cm) x D: 2.3 in (5.84 cm)

Reference Connection QTHA-2MSA

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Female Quick-test
Weight	1.54 oz / 44 grams
Dimensions	H: 1.68 in (4.27 cm) x W: 0.7 in (1.78 cm) x D: 0.7 in (1.78 cm)

Process Connection (Qty 2) QTHA-2MS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N

Process Connection (Qty 2) QTHA-2MS0

Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	1.01 oz / 29 grams
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)

Hose 1 QSQS-HOS-6m

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	6 m / 19.69 ft
Inner Diameter	0.08 In / 3.00 mm
Length	6.00 m / 19 ft 8 in
Materials	Reinforced Polyamide, Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	5.33 oz / 150 grams

Hose 2 QSQS-HOS-1m

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	1 m / 3.28 ft
Inner Diameter	0.08 In / 3.00 mm
Length	1.00 m / 3 ft 3 in
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa

Hose 2 QSQS-HOS-1m

Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	2.53 oz / 72 grams

Bag SM-0027

Materials	Zippered Nylon
Country of origin	USA
Weight	3 oz / 85 grams
Dimensions	H: 10 in (25.4 cm) x W: 2 in (5.08 cm) x D: 9 in (22.86 cm)