

Part No.

QTCM-0000-0-0

QTCM manifold only, no gauge adapter, no hoses, no process connections, no bag

The most economical way of performing static pressure calibrations in the field using nitrogen or other compressed gas.



QTCM-0000-0-0

Included Items

- Manifold - QTCM Brass Calibration Manifold (QTCM)

Specs/Attributes

Max Pressure	3000 PSI / 200 bar / 20 MPa
Materials	Brass
Seal Materials	Buna-N, Delrin, Teflon
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Hose 1	None
Hose 2	None
Pressure Reference	None
Process Connection	None
Reference Connection	None
Country of origin	USA
Weight	1.46 lbs / 660 grams
Dimensions	H: 3.78 in (9.6 cm) x W: 5.16 in (13.11 cm) x D: 2.63 in (6.68 cm)

Manifold QTCM

Max Pressure	3000 PSI / 200 bar / 20 MPa
Min Operating Temperature	0 °F / -18 °C

Manifold QTCM

Max Operating Temperature	130 °F / 54 °C
Fine Adjustment Resolution	0.10 PSI / 0.69 mbar / 0.00 kPa
Harmonized Code	9032.81.0060
Country of origin	USA
Pressure Media	Nitrogen, inert gas
Inlet Port	Male Quick-test
Materials	Anodized Aluminum, Brass
Media Compatibility	Air, Inert Gas, Natural Gas
Outlet Port	Male Quick-test
Seal Materials	Buna-N, Delrin, Teflon
Burst Pressure	12000 PSI / 825 bar / 83 MPa
Weight	2.20 lbs / 1000 grams
Dimensions	H: 3.8 in (9.65 cm) x W: 5.1 in (12.95 cm) x D: 2.3 in (5.84 cm)