Part No.

## **QTCM-1MBA-20-2**

QTCM manifold, 1/8" MNPT gauge adapter, 20ft, 2ft hoses, (2) 1/4" MNPT process conn., nylon bag

Attach a gauge or pressure calibrator directly to the calibration manifold and easily perform static pressure calibrations (pressure gauge not included)



QTCM-1MBA-20-2

## **Included Items**

- Manifold QTCM Assembly (QTCM)
- Gauge Swivel 1/8" male NPT x female Quick-test, no check-valve, brass (QTHA-1MBA)
- Process Connection 1 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Hose 1 Quick-test 6900 psi hose, brass hose ends, 20 ft (6.10 m) long (QTQT-HOS-20ft)
- Hose 2 Quick-test 6900 psi hose, brass hose ends, 2 ft (61 cm) long (QTQT-HOS-2ft)
- Storage Bag Zippered bag to hold hose and adapters, nylon (QTHA-HSBG)

## **Specs/Attributes**

•	
Burst Pressure	27000 PSI
Color	Silver
Fine Adjustment Resolution	0.1 PSI
Fluid Media	Air,Inert Gas,Natural Gas,Petroleum Based Oil,Water
Has Check Valve	No
Hose 1	Quick-test Hose, Brass ends, 20ft / 6.1m long
Hose 2	Quick-test Hose, Brass ends, 2ft / 0.6m long
Inlet Port	Male Quick-test
Inner Diameter	0.08 In
Length	20, 2 ft
Materials	Anodized Aluminum, Brass
Max Pressure	3000 PSI
Max Temperature	130 °F
Max Vacuum	In Hg



## **Specs/Attributes**

Media Compatibility	Air, Inert Gas, Natural Gas
Min Temperature	0 °F
Minimum Bend Radius	1 ln
Outer Diameter	0.2 ln
Outlet Port	Male Quick-test
Pressure Reference	None
Process Connection	1/4" Male NPT
Reference Connection	1/8" Male NPT
Seal Materials	Buna-N, Delrin, Teflon
Туре	QT
Wrench Size	9/16 ln 15 mm