Ralston

Part No.

QTFT-FRS0-VT

5/16"-24 UNF x male Quick-test, with cap and chain, S.S., Viton seals

Ideal for situations where frequent calibration of a DP transmitter using the bleeder port is required

QTFT-FRS0-VT

Specs/Attributes

Compatible with	Anderson Greenwood M25 Block and Bleed Valves, Anderson Greenwood M251 Block and Bleed Valves, Rosemount 2051 Series DP Pressure Transmitters, Rosemount 3051 Series DP Pressure Transmitters, Yokogawa EJ series DP Pressure Transmitters
Country of origin	USA
Materials	Stainless Steel
Max Operating Temperature	400 °F / 205 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-15 °F / -26 °C
Seal Materials	Viton
Wrench Size	15 mm 9/16 In
Connector End 1	Male Quick-test
Connector End 2	5/16-24 Male DP Transmitter/Gauge valve
Weight	1.92 oz / 54 grams
Dimensions	H: 2.7 in (6.86 cm) x W: 0.7 in (1.78 cm) x D: 0.7 in (1.78 cm)