

Part No.

QTHA-2MS0-B341T03-QD

Cylinder adapter, BS341 TYPE 3 - Quick-connect x 1/4" Male NPT adapter, S.S.

Connect to any BS 341 Type 3 valve on high pressure compressed gas cylinders. BS 341 is a UK standard.



QTHA-2MS0-B341T03-QD

Specs/Attributes

Certifications	BS 341 Type 3 (United Kingdom)
Country of origin	USA
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Urethane
Connector End 1	Type 3 Male BS 341
Connector End 2	1/4" Male NPT (ASME B1.20.1)
Weight	11.18 oz / 315 grams
Dimensions	H: 4.25 in (10.8 cm) x W: 1.45 in (3.68 cm) x D: 1.45 in (3.68 cm)