

Part No.

 QTHA-KIT16-SS-15ft

# QTHA-KIT16-SS-15ft

(1) QSQS-HOS-15ft hose with S.S. ends, 15ft long, (2)  
QTHA-2TB0 (1/4" Tube X Male Quick-test, brass)

15 ft hose with 1/4" tube adapters on each end.

## Included Items

- Hose - Quick-test 6900 psi hose, S.S. hose ends, 15 ft long (QSQS-HOS-15ft)
- Adapter (Qty 2) - 1/4" tube fitting x male Quick-test, no check-valve, brass (QTHA-2TB0)

## Specs/Attributes

|                   |                                                              |
|-------------------|--------------------------------------------------------------|
| Country of origin | USA                                                          |
| Weight            | 3.5 oz / 99 grams                                            |
| Dimensions        | H: 12 in (30.48 cm) x W: 9 in (22.86 cm) x D: 1 in (2.54 cm) |

## Hose QSQS-HOS-15ft

|                           |                                                         |
|---------------------------|---------------------------------------------------------|
| Burst Pressure            | 27000 PSI / 1860 bar / 185 MPa                          |
| Color                     | Silver                                                  |
| Country of origin         | USA                                                     |
| Fluid Media               | Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water |
| Hose Length               | 10 ft / 3.05 m                                          |
| Inner Diameter            | 0.08 In / 3.00 mm                                       |
| Length                    | 10 ft / 4.00 m                                          |
| Materials                 | Stainless Steel                                         |
| Max Operating Temperature | 140 °F / 60 °C                                          |
| Max Pressure              | 6900 PSI / 475 bar / 48 MPa                             |
| Max Vacuum                | -30.00 InHg / -101.6 kPa                                |
| Media Compatibility       | Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water |
| Min Operating Temperature | -40 °F / -40 °C                                         |
| Minimum Bend Radius       | 1.00 In / 26 mm                                         |
| Outer Diameter            | 0.20 In / 6.00 mm                                       |
| Type                      | QT                                                      |
| Weight                    | 4.45 oz / 125 grams                                     |

## Adapter (Qty 2) QTHA-2TB0

|                   |       |
|-------------------|-------|
| Country of origin | USA   |
| Has Check Valve   | No    |
| Materials         | Brass |

**Adapter (Qty 2)** QTHA-2TB0

|                           |                                                                    |
|---------------------------|--------------------------------------------------------------------|
| Max Operating Temperature | 225 °F / 105 °C                                                    |
| Max Pressure              | 5000 PSI / 350 bar / 35 MPa                                        |
| Max Vacuum                | 0.00 InHg / 0.0 kPa                                                |
| Seal Materials            | Buna-N                                                             |
| Connector End 1           | 1/4" Male Tube Fitting                                             |
| Connector End 2           | Male Quick-test                                                    |
| Weight                    | 1.17 oz / 33 grams                                                 |
| Dimensions                | H: 1.47 in (3.73 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm) |