

Part No.

 QTHA-KIT16-SS-4ft

QTHA-KIT16-SS-4ft

(1) QSQS-HOS-4ft hose with S.S. ends, 4ft long, (2) QTHA-2TB0 (1/4" Tube X Male Quick-test, brass)

4 ft hose with 1/4" tube adapters on each end.

Included Items

- Hose - Quick-test 6900 psi hose, S.S. hose ends, 4 ft (122 cm) long (QSQS-HOS-4ft)
- Adapter (Qty 2) - 1/4" tube fitting x male Quick-test, no check-valve, brass (QTHA-2TB0)

Specs/Attributes

Hose Length	4 ft / 122 cm
Weight	5.2 oz / 145 grams
Dimensions	H: 8 in (20.32 cm) x W: 5 in (12.7 cm) x D: 1 in (2.54 cm)

Hose QSQS-HOS-4ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	4 ft / 122 cm
Inner Diameter	0.08 In / 3.00 mm
Length	4 ft / 2.00 m
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	2.64 oz / 75 grams

Adapter (Qty 2) QTHA-2TB0

Country of origin	USA
Has Check Valve	No

Adapter (Qty 2) QTHA-2TB0

Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Connector End 1	1/4" Male Tube Fitting
Connector End 2	Male Quick-test
Weight	1.17 oz / 33 grams
Dimensions	H: 1.47 in (3.73 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)