

Part No.

 QTHA-KIT16-SS-6ft

# QTHA-KIT16-SS-6ft

(1) QSQS-HOS-6ft hose with S.S. ends, 6ft long, (2)  
QTHA-2TB0 (1/4" Tube X Male Quick-test, brass)

6 ft hose with 1/4" tube adapters on each end.

## Included Items

- Hose - Quick-test 6900 psi hose, S.S. hose ends, 6 ft (1.83 m) long (QSQS-HOS-6ft)
- Adapter - 1/4" tube fitting x male Quick-test, no check-valve, brass (QTHA-2TB0)
- Adapter - 1/4" tube fitting x male Quick-test, no check-valve, brass (QTHA-2TB0)

## Specs/Attributes

Weight	5.38 oz / 155 grams
Dimensions	H: 12 in (30.48 cm) x W: 9 in (22.86 cm) x D: 1 in (2.54 cm)

## Hose QSQS-HOS-6ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	6 ft / 1.83 m
Inner Diameter	0.08 In / 3.00 mm
Length	6 ft / 2.00 m
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	2.98 oz / 84 grams

## Adapter QTHA-2TB0

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C

**Adapter** QTHA-2TB0

Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Connector End 1	1/4" Male Tube Fitting
Connector End 2	Male Quick-test
Weight	1.17 oz / 33 grams
Dimensions	H: 1.47 in (3.73 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)