

Part No.

 **QTHA-KIT18-SS**

QTHA-KIT18-SS

Hose and fitting calibration kit, stainless steel

3 ft and 6 ft Quick-test hoses with a variety of adapters and a tee

Included Items

- Bag - Zippered bag to hold hose and adapters, nylon (SM-0027)
- Adapter (Qty 3) - 1/4" tube fitting x male Quick-test, no check-valve, S.S. (QTHA-2TS0)
- Adapter - 3/8" tube fitting x male Quick-test, no check-valve, S.S. (QTHA-3TS0)
- Adapter - 1/2" tube fitting x male Quick-test, no check-valve, S.S. (QTHA-4TS0)
- Adapter - 1/4" female NPT x male Quick-test, no check-valve, S.S. (QTHA-2FS0)
- Adapter - 1/4" male NPT QD (Quick-connect) Adapter, S.S. (QTHA-2MS0-QD)
- Adapter - 5/16"-24 UNF x male Quick-test, no check-valve, S.S. (QTHA-FRS0)
- Tee - Male Quick-test run x male Quick-test run x male Quick-test branch tee, S.S. (QTHA-HSTS)
- Adapter - 1/2" female NPT x male Quick-test, no check-valve, S.S. (QTHA-4FS0)
- Hose (Qty 3) - Quick-test 6900 psi hose, S.S. hose ends, 3 ft (92 cm) long (QSQS-HOS-3ft)
- Hose - Quick-test 6900 psi hose, S.S. hose ends, 6 ft (1.83 m) long (QSQS-HOS-6ft)

Specs/Attributes

Country of origin	USA
Weight	5.38 oz / 155 grams
Dimensions	H: 12 in (30.48 cm) x W: 9 in (22.86 cm) x D: 1 in (2.54 cm)

Bag SM-0027

Materials	Zippered Nylon
Country of origin	USA
Weight	3 oz / 85 grams
Dimensions	H: 10 in (25.4 cm) x W: 2 in (5.08 cm) x D: 9 in (22.86 cm)

Adapter (Qty 3) QTHA-2TS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Connector End 1	1/4" Male Tube Fitting

Adapter (Qty 3) QTHA-2TS0

Connector End 2	Male Quick-test
Weight	1.06 oz / 30 grams
Dimensions	H: 1.47 in (3.73 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)

Adapter QTHA-4FS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	1-1/8 In 29 mm
Connector End 1	1/2" Female NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	4.72 oz / 135 grams
Dimensions	H: 1.66 in (4.22 cm) x W: 1.12 in (2.84 cm) x D: 1.12 in (2.84 cm)

Tee QTHA-HSTS

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Connector End 1	Male Quick-test
Connector End 2	Male Quick-test
Connector End 3	Male Quick-test
Weight	1.89 oz / 54 grams
Dimensions	H: 1.96 in (4.98 cm) x W: 1.25 in (3.18 cm) x D: 1.25 in (3.18 cm)

Hose (Qty 3) QSQS-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver

Hose (Qty 3) QSQS-HOS-3ft

Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	3ft / 0.91 m
Inner Diameter	0.08 In / 3.00 mm
Length	3 ft / 92 cm
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	2.48 oz / 70 grams

Hose QSQS-HOS-6ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	6 ft / 1.83 m
Inner Diameter	0.08 In / 3.00 mm
Length	6 ft / 2.00 m
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	2.98 oz / 84 grams