

Part No.

QTHA-KIT26

Ralston Quick-test BSPP Gauge Mount Kit

Pressure gauge connection kit for direct manifold or pump mount when calibrating pressure gauges with BSPP connections using Ralston benchtop manifolds



QTHA-KIT26

Included Items

- 1/4" Female BSPP - 1/4" female BSPP Quick-disconnect x female Quick-test, S.S. (QTHA-2FSA-RG-QD)
- 3/8" Female BSPP - 3/8" female BSPP quick-disconnect x female Quick-test, S.S. (QTHA-3FSA-RG-QD)
- 1/2" Female BSPP - 1/2" female BSPP quick-disconnect x female Quick-test, S.S. (QTHA-4FSA-RG-QD)
- Bag - Zippered bag to hold hose and adapters, nylon (SM-0084)

1/4" Female BSPP QTHA-2FSA-RG-QD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Teflon
Dimensions	H: 2 in (5.08 cm) x W: 0.95 in (2.41 cm)

3/8" Female BSPP QTHA-3FSA-RG-QD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa

3/8" Female BSPP QTHA-3FSA-RG-QD

Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Teflon
Dimensions	H: 1.97 in (5 cm) x W: 1.37 in (3.48 cm)

1/2" Female BSPP QTHA-4FSA-RG-QD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Teflon
Dimensions	H: 1.95 in (4.95 cm) x W: 1.38 in (3.51 cm)

Bag SM-0084

Max Pressure	0.00 PSI / 0.00 mbar / 0.00 kPa
Max Vacuum	0.00 InHg / 0.0 kPa
Materials	Zippered Nylon
Country of origin	USA