

Part No.

 **QTHA-KIT39**

QTHA-KIT39

Hose and adapter conversion kit for Ametek T-970 and T-975

Hose and adapter conversion kit for Ametek T-970 and T-975

Included Items

- Adapter - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Bonded seal - 3/8" male RS bonded seal ring, steel and Buna-N (QTHA-3BR-RS)
- Hose - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)
- Adapter - G 3/8" male BSPP (ISO 228/1) x male Quick-test, no check-valve, brass (QTHA-3MB0-RS)
- Adapter - QTVC Outlet port, male Quick-test, brass (QTHA-5SB0)
- Adapter - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)

Specs/Attributes

Weight	9.47 oz / 270 grams
Dimensions	H: 12 in (30.48 cm) x W: 9 in (22.86 cm) x D: 1 in (2.54 cm)

Adapter QTHA-2MB0

Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Country of origin	USA
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	1.09 oz / 31 grams
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)

Bonded seal QTHA-3BR-RS

Max Pressure	0.00 PSI / 0.00 mbar / 0.00 kPa
Max Vacuum	0.00 InHg / 0.0 kPa
Materials	Plated Steel
Seal Materials	Buna-N
Country of origin	USA

Bonded seal QTHA-3BR-RS

Weight	0.1 oz / 2.83 grams
Dimensions	H: 0.94 in (2.39 cm) x W: 0.12 in (0.3 cm) x D: 0.12 in (0.3 cm)

Hose QTQT-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	3ft / 0.91 m
Inner Diameter	0.08 In / 3.00 mm
Length	3 ft / 92 cm
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	2.68 oz / 76 grams