

Part No.

QTHA-KIT4-SS

Universal Quick-test hose and adapter kit (20 stainless steel adapters, 2 hoses)

Kits take the guesswork out of selecting adapters by providing a selection of the most popular combinations of hoses and adapters



QTHA-KIT4-SS

Included Items

- 1/8" male NPT adapter, S.S. - 1/8" male NPT x male Quick-test, no check-valve, S.S. (QTHA-1MS0)
- 1/8" male NPT Quick-connect adapter, S.S. - 1/8" male NPT QD (Quick-connect) Adapter, S.S. (QTHA-1MS0-QD)
- 1/4" male NPT adapter, S.S. - 1/4" male NPT x male Quick-test, no check-valve, S.S. (QTHA-2MS0)
- 1/4" male NPT Quick-connect adapter, S.S. - 1/4" male NPT QD (Quick-connect) Adapter, S.S. (QTHA-2MS0-QD)
- 3/8" male NPT adapter, S.S. - 3/8" male NPT x male Quick-test, no check-valve, S.S. (QTHA-3MS0)
- 1/2" male NPT adapter, S.S. - 1/2" male NPT x male Quick-test, no check-valve, S.S. (QTHA-4MS0)
- 1/8" female NPT adapter, S.S. - 1/8" female NPT x male Quick-test, no check-valve, S.S. (QTHA-1FS0)
- 1/8" female Quick-connect adapter, S.S. - 1/8" female NPT Quick-connect x male Quick-test, no check-valve, S.S. (QTHA-1FS0-QD)
- 1/4" female NPT adapter, S.S. - 1/4" female NPT x male Quick-test, no check-valve, S.S. (QTHA-2FS0)
- 1/4" female NPT Quick-connect adapter, S.S. - 1/4" female NPT Quick-connect x male Quick-test, no check-valve, S.S. (QTHA-2FS0-QD)
- 3/8" female NPT adapter, S.S. - 3/8" female NPT x male Quick-test, no check-valve, S.S. (QTHA-3FS0)
- 1/2" female NPT adapter, S.S. - 1/2" female NPT x male Quick-test, no check-valve, S.S. (QTHA-4FS0)
- 1/2" female NPT Quick-connect adapter, S.S. - 1/2" female NPT Quick-connect x male Quick-test, no check-valve, S.S. (QTHA-4FS0-QD)
- 1/4" tube adapter, S.S. - 1/4" tube fitting x male Quick-test, no check-valve, S.S. (QTHA-2TS0)
- 3/8" tube adapter, S.S. - 3/8" tube fitting x male Quick-test, no check-valve, S.S. (QTHA-3TS0)
- 1/2" tube adapter, S.S. - 1/2" tube fitting x male Quick-test, no check-valve, S.S. (QTHA-4TS0)
- 5/16"-24 UNF DP Transmitter adapter, S.S. - 5/16"-24 UNF x male Quick-test, no check-valve, S.S. (QTHA-FRS0)
- 1/4"-28 UNF DP Transmitter adapter, S.S. - 1/4"-28 UNF x male Quick-test, no check-valve, S.S. (QTHA-HNS0)
- Quick-test tee, S.S. - Male Quick-test run x male Quick-test run x male Quick-test branch tee, S.S. (QTHA-HSTS)
- Male Quick-test union, S.S. - Male Quick-test x male Quick-test hose union, S.S. (QTHA-HHSU)
- Quick-test hose, S.S. ends, 6ft long - Quick-test 6900 psi hose, S.S. hose ends, 6 ft (1.83 m) long (QSQS-HOS-6ft)
- Quick-test hose, S.S. ends, 3ft long - Quick-test 6900 psi hose, S.S. hose ends, 3 ft (92 cm) long (QSQS-HOS-3ft)
- Case and foam - Case and foam for hose and adapter kits, empty (AS-QTHA-KIT4)

Specs/Attributes

Materials	Stainless Steel
Seal Materials	Buna-N, Teflon
Country of origin	USA
Weight	9.38 lbs / 4.26 kg
Dimensions	H: 17.5 in (44.45 cm) x W: 11.25 in (28.58 cm) x D: 5.25 in (13.34 cm)

1/8" male NPT adapter, S.S. QTHA-1MS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/8" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	0.8 oz / 23 grams
Dimensions	H: 1.2 in (3.05 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)

1/8" male NPT Quick-connect adapter, S.S. QTHA-1MS0-QD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Teflon
Connector End 1	1/8" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	2.22 oz / 63 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 0.87 in (2.21 cm) x D: 0.87 in (2.21 cm)

1/4" male NPT adapter, S.S. QTHA-2MS0

Country of origin	USA
-------------------	-----

1/4" male NPT adapter, S.S. QTHA-2MS0

Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	1.01 oz / 29 grams
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)

1/4" male NPT Quick-connect adapter, S.S. QTHA-2MS0-QD

Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Country of origin	USA
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Seal Materials	Buna-N, Teflon
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	3.55 oz / 100 grams
Dimensions	H: 1.88 in (4.78 cm) x W: 1 in (2.54 cm) x D: 1 in (2.54 cm)

3/8" male NPT adapter, S.S. QTHA-3MS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	3/4 In 19 mm

3/8" male NPT adapter, S.S. QTHA-3MS0

Connector End 1	3/8" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	1.81 oz / 51 grams
Dimensions	H: 1.4 in (3.56 cm) x W: 0.75 in (1.91 cm) x D: 0.75 in (1.91 cm)

1/2" male NPT adapter, S.S. QTHA-4MS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	7/8 In 23 mm
Connector End 1	1/2" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	3.49 oz / 99 grams
Dimensions	H: 1.57 in (3.99 cm) x W: 0.87 in (2.21 cm) x D: 0.87 in (2.21 cm)

1/8" female NPT adapter, S.S. QTHA-1FS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Wrench Size	5/8 In 16 mm
Connector End 1	1/8" Female NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	1.42 oz / 40 grams
Dimensions	H: 1.38 in (3.51 cm) x W: 0.62 in (1.57 cm) x D: 0.62 in (1.57 cm)

1/8" female Quick-connect adapter, S.S. QTHA-1FS0-QD

Country of origin	USA
Has Check Valve	No

1/8" female Quick-connect adapter, S.S. QTHA-1FS0-QD

Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Teflon
Connector End 1	1/8" Female NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	1.9 oz / 54 grams
Dimensions	H: 1.52 in (3.86 cm) x W: 0.78 in (1.98 cm) x D: 0.78 in (1.98 cm)

1/4" female NPT adapter, S.S. QTHA-2FS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Wrench Size	3/4 In 19 mm
Connector End 1	1/4" Female NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	2.1 oz / 60 grams
Dimensions	H: 1.57 in (3.99 cm) x W: 0.75 in (1.91 cm) x D: 0.75 in (1.91 cm)

1/4" female NPT Quick-connect adapter, S.S. QTHA-2FS0-QD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Teflon
Connector End 1	1/4" Female NPT (ASME B1.20.1)

1/4" female NPT Quick-connect adapter, S.S. QTHA-2FS0-QD

Connector End 2	Male Quick-test
Weight	2.61 oz / 74 grams
Dimensions	H: 1.67 in (4.24 cm) x W: 0.94 in (2.39 cm) x D: 0.94 in (2.39 cm)

3/8" female NPT adapter, S.S. QTHA-3FS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	15/16 In 24 mm
Connector End 1	3/8" Female NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	3.04 oz / 86 grams
Dimensions	H: 1.32 in (3.35 cm) x W: 0.94 in (2.39 cm) x D: 0.94 in (2.39 cm)

1/2" female NPT adapter, S.S. QTHA-4FS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	1-1/8 In 29 mm
Connector End 1	1/2" Female NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	4.72 oz / 135 grams
Dimensions	H: 1.66 in (4.22 cm) x W: 1.12 in (2.84 cm) x D: 1.12 in (2.84 cm)

1/2" female NPT Quick-connect adapter, S.S. QTHA-4FS0-QD

Country of origin	USA
Has Check Valve	No

1/2" female NPT Quick-connect adapter, S.S. QTHA-4FS0-QD

Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Teflon
Connector End 1	1/2" Female NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	5.26 oz / 150 grams
Dimensions	H: 1.69 in (4.29 cm) x W: 1.39 in (3.53 cm) x D: 1.39 in (3.53 cm)

1/4" tube adapter, S.S. QTHA-2TS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Connector End 1	1/4" Male Tube Fitting
Connector End 2	Male Quick-test
Weight	1.06 oz / 30 grams
Dimensions	H: 1.47 in (3.73 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)

3/8" tube adapter, S.S. QTHA-3TS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Connector End 1	3/8" Male Tube Fitting
Connector End 2	Male Quick-test
Weight	9.19 lbs / 4.17 kg

3/8" tube adapter, S.S. QTHA-3TS0

Dimensions	H: 1.53 in (3.89 cm) x W: 0.72 in (1.83 cm) x D: 0.72 in (1.83 cm)
------------	--

1/2" tube adapter, S.S. QTHA-4TS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Connector End 1	1/2" Male Tube Fitting
Connector End 2	Male Quick-test
Weight	2.66 oz / 75 grams
Dimensions	H: 1.7 in (4.32 cm) x W: 1 in (2.54 cm) x D: 1 in (2.54 cm)

5/16-24 UNF DP Transmitter adapter, S.S. QTHA-FRS0

Compatible with	Rosemount 2051 Series DP Pressure Transmitters, Rosemount 3051 Series DP Pressure Transmitters, Yokogawa EJ series DP Pressure Transmitters, Anderson Greenwood M25 Block and Bleed Valves, Anderson Greenwood M251 Block and Bleed Valves
Country of origin	USA
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	5/16-24 Male DP Transmitter/Gauge valve
Connector End 2	Male Quick-test
Weight	1.17 oz / 33 grams
Dimensions	H: 2.16 in (5.49 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)

1/4-28 UNF DP Transmitter adapter, S.S. QTHA-HNS0

Compatible with	Honeywell Smartline ST700 Pressure Transmitter, Honeywell Smartline ST800 Pressure Transmitter
Country of origin	USA

1/4-28 UNF DP Transmitter adapter, S.S. QTHA-HNS0

Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/4-28 Male DP Transmitter/Gauge valve
Connector End 2	Male Quick-test
Weight	0.94 oz / 27 grams
Dimensions	H: 2.02 in (5.13 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)

Quick-test tee, S.S. QTHA-HSTS

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Connector End 1	Male Quick-test
Connector End 2	Male Quick-test
Connector End 3	Male Quick-test
Weight	1.89 oz / 54 grams
Dimensions	H: 1.96 in (4.98 cm) x W: 1.25 in (3.18 cm) x D: 1.25 in (3.18 cm)

Male Quick-test union, S.S. QTHA-HHSU

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa

Male Quick-test union, S.S. QTHA-HHSU

Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	Male Quick-test
Connector End 2	Male Quick-test
Weight	1.06 oz / 30 grams
Dimensions	H: 1.25 in (3.18 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)

Quick-test hose, S.S. ends, 6ft long QSQS-HOS-6ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	6 ft / 1.83 m
Inner Diameter	0.08 In / 3.00 mm
Length	6 ft / 2.00 m
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	2.98 oz / 84 grams

Quick-test hose, S.S. ends, 3ft long QSQS-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	3ft / 0.91 m
Inner Diameter	0.08 In / 3.00 mm
Length	3 ft / 92 cm
Materials	Stainless Steel

Quick-test hose, S.S. ends, 3ft long QSQS-HOS-3ft

Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	2.48 oz / 70 grams

Case and foam AS-QTHA-KIT4

Materials	ABS Plastic
Country of origin	USA