

Part No.

QTHA-KIT6-3ft

Quick-test hose kit - (2) 3 ft hoses, (2) 1/8" MNPT, (2) 1/4" MNPT adapters, brass

Kits take the guesswork out of selecting adapters by providing a selection of the most popular combinations of hoses and adapters



QTHA-KIT6-3ft

Included Items

- Adapter - 1/8" male NPT x male Quick-test, no check-valve, brass (QTHA-1MB0)
- Adapter - 1/8" male NPT x male Quick-test, no check-valve, brass (QTHA-1MB0)
- Adapter - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Adapter - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Hose 1 - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)
- Hose 2 - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)

Specs/Attributes

| | |
|--------------------|--|
| Materials | Brass |
| Seal Materials | Buna-N |
| Max Pressure | 5000 PSI / 350 bar / 35 MPa |
| Country of origin | USA |
| Number of Adapters | 4 |
| Number of Hoses | 2 |
| Weight | 8.38 oz / 240 grams |
| Dimensions | H: 12 in (30.48 cm) x W: 9 in (22.86 cm) x D: 1 in (2.54 cm) |

Adapter QTHA-2MB0

| | |
|---------------------------|--------------------------------|
| Burst Pressure | 20000 PSI / 1380 bar / 140 MPa |
| Country of origin | USA |
| Materials | Brass |
| Max Operating Temperature | 225 °F / 105 °C |

Adapter QTHA-2MB0

| | |
|---------------------------|--|
| Max Pressure | 5000 PSI / 350 bar / 35 MPa |
| Max Vacuum | 0.00 InHg / 0.0 kPa |
| Min Operating Temperature | 0 °F / -18 °C |
| Seal Materials | Buna-N |
| Wrench Size | 9/16 In 15 mm |
| Connector End 1 | 1/4" Male NPT (ASME B1.20.1) |
| Connector End 2 | Male Quick-test |
| Weight | 1.09 oz / 31 grams |
| Dimensions | H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm) |

Hose 1 QTQT-HOS-3ft

| | |
|---------------------------|---|
| Burst Pressure | 27000 PSI / 1860 bar / 185 MPa |
| Color | Silver |
| Country of origin | USA |
| Fluid Media | Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water |
| Hose Length | 3ft / 0.91 m |
| Inner Diameter | 0.08 In / 3.00 mm |
| Length | 3 ft / 92 cm |
| Materials | Brass |
| Max Operating Temperature | 140 °F / 60 °C |
| Max Pressure | 6900 PSI / 475 bar / 48 MPa |
| Max Vacuum | -30.00 InHg / -101.6 kPa |
| Media Compatibility | Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water |
| Min Operating Temperature | -40 °F / -40 °C |
| Minimum Bend Radius | 1.00 In / 26 mm |
| Outer Diameter | 0.20 In / 6.00 mm |
| Type | QT |
| Weight | 2.68 oz / 76 grams |

Hose 2 QTQT-HOS-3ft

| | |
|-------------------|---|
| Burst Pressure | 27000 PSI / 1860 bar / 185 MPa |
| Color | Silver |
| Country of origin | USA |
| Fluid Media | Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water |
| Hose Length | 3ft / 0.91 m |
| Inner Diameter | 0.08 In / 3.00 mm |
| Length | 3 ft / 92 cm |
| Materials | Brass |

Hose 2 QTQT-HOS-3ft

| | |
|---------------------------|---|
| Max Operating Temperature | 140 °F / 60 °C |
| Max Pressure | 6900 PSI / 475 bar / 48 MPa |
| Max Vacuum | -30.00 InHg / -101.6 kPa |
| Media Compatibility | Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water |
| Min Operating Temperature | -40 °F / -40 °C |
| Minimum Bend Radius | 1.00 In / 26 mm |
| Outer Diameter | 0.20 In / 6.00 mm |
| Type | QT |
| Weight | 2.68 oz / 76 grams |