

Part No.

# QTVC-1MBA-2m-1m

*Precision volume controller, 1/8" male NPT gauge connection, 6' inlet, 3' outlet hoses*

Calibrate both very low pressure or high pressure instrumentation using nitrogen with an attached pressure gauge or calibrator (gauge or calibrator not included)



QTVC-1MBA-2m-1m

## Included Items

- Volume Controller - QTVC Volume Controller (QTVC)
- Reference Connection - 1/8" male NPT x female Quick-test, no check-valve, brass (QTHA-1MBA)
- Process Connection 1 - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Process Connection 2 - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Hose 1 - Quick-test 6900 psi hose, brass hose ends, 2 m (6.6 ft) long (QTQT-HOS-2m)
- Hose 2 - Quick-test 6900 psi hose, brass hose ends, 1 m (3.3 ft) long (QTQT-HOS-1m)

## Specs/Attributes

Materials	Anodized Aluminum, Brass, Powder Coated Steel, Stainless Steel
Seal Materials	Buna-N, Delrin, Teflon
Max Pressure	3000 PSI / 200 bar / 20 MPa
Max Vacuum	10 InHg / 33.9 kPa
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Hose 1	Quick-test Hose, Brass ends, 2m long
Hose 2	Quick-test Hose, Brass ends, 1m long
Pressure Reference	None
Process Connection	1/4" Male NPT
Reference Connection	1/8" Male NPT
Country of origin	USA
Weight	6.00 lbs / 2.72 kg
Dimensions	H: 6.16 in (15.65 cm) x W: 8.5 in (21.59 cm) x D: 7.38 in (18.75 cm)

## Volume Controller QTVC

Harmonized Code	9032.81.0060
-----------------	--------------

## Volume Controller QTVC

Inlet Port	Male Quick-test
Outlet Port	Male Quick-test, Male Quick-test with cap and chain
Max Pressure	3000 PSI / 200 bar / 20 MPa
Max Vacuum	10 InHg / 33.9 kPa
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Pressure Media	Nitrogen, inert gas
Fine Adjustment Resolution	0.00 PSI / 0.00 mbar / 0.00 kPa
Mechanical Rotation	42 turns (pressure balanced)
Materials	Anodized Aluminum, Brass, Powder Coated Steel, Stainless Steel
Media Compatibility	Air, Inert Gas, Natural Gas
Seal Materials	Buna-N, Delrin, Teflon
Country of origin	USA
Weight	3.70 lbs / 1.68 kg
Dimensions	H: 6.8 in (17.27 cm) x W: 8.5 in (21.59 cm) x D: 6.6 in (16.76 cm)

## Reference Connection QTHA-1MBA

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Wrench Size	9/16 In 15 mm
Connector End 1	1/8" Male NPT (ASME B1.20.1)
Connector End 2	Female Quick-test
Dimensions	H: 1.55 in (3.94 cm) x W: 0.7 in (1.78 cm)

## Process Connection 1 QTHA-2MB0

Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Country of origin	USA
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C

### Process Connection 1 QTHA-2MB0

Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm)

### Process Connection 2 QTHA-2MB0

Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Country of origin	USA
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm)

### Hose 1 QTQT-HOS-2m

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	2 m / 6.56 ft
Inner Diameter	0.08 In / 3.00 mm
Length	2.00 m / 6 ft 7 in
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT

**Hose 2** QTQT-HOS-1m

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	1 m / 3.28 ft
Inner Diameter	0.08 In / 3.00 mm
Length	1.00 m / 3 ft 3 in
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT