

Part No.

QTVC-2MBA-2m-1m

Precision volume controller, 1/4" male NPT gauge connection, 6' inlet, 3' outlet hoses

Calibrate both very low pressure or high pressure instrumentation using nitrogen with an attached pressure gauge or calibrator (gauge or calibrator not included)



QTVC-2MBA-2m-1m

Included Items

- Volume Controller - QTVC Volume Controller (QTVC)
- Reference Connection - 1/4" male NPT x female Quick-test, no check-valve, brass (QTHA-2MBA)
- Process Connection 1 - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Process Connection 2 - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Hose 1 - Quick-test 6900 psi hose, brass hose ends, 2 m (6.6 ft) long (QTQT-HOS-2m)
- Hose 2 - Quick-test 6900 psi hose, brass hose ends, 1 m (3.3 ft) long (QTQT-HOS-1m)

Specs/Attributes

Materials	Anodized Aluminum, Brass, Powder Coated Steel, Stainless Steel
Seal Materials	Buna-N, Delrin, Teflon
Max Pressure	3000 PSI / 200 bar / 20 MPa
Max Vacuum	10 InHg / 33.9 kPa
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Country of origin	USA
Hose 1	Quick-test Hose, Brass ends, 2m long
Hose 2	Quick-test Hose, Brass ends, 1m long
Pressure Reference	None
Process Connection	1/4" Male NPT
Reference Connection	1/4" Male NPT
Weight	6.00 lbs / 2.72 kg
Dimensions	H: 6.16 in (15.65 cm) x W: 8.5 in (21.59 cm) x D: 7.38 in (18.75 cm)

Volume Controller QTVC

Volume Controller QTVC

Harmonized Code	9032.81.0060
Inlet Port	Male Quick-test
Outlet Port	Male Quick-test, Male Quick-test with cap and chain
Max Pressure	3000 PSI / 200 bar / 20 MPa
Max Vacuum	10 InHg / 33.9 kPa
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Fine Adjustment Resolution	0.00 PSI / 0.00 mbar / 0.00 kPa
Mechanical Rotation	42 turns (pressure balanced)
Materials	Anodized Aluminum, Brass, Powder Coated Steel, Stainless Steel
Media Compatibility	Air, Inert Gas, Natural Gas
Seal Materials	Buna-N, Delrin, Teflon
Country of origin	USA
Weight	3.70 lbs / 1.68 kg
Dimensions	H: 6.8 in (17.27 cm) x W: 8.5 in (21.59 cm) x D: 6.6 in (16.76 cm)

Reference Connection QTHA-2MBA

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Female Quick-test
Weight	1.6 oz / 45 grams
Dimensions	H: 1.68 in (4.27 cm) x W: 0.7 in (1.78 cm) x D: 0.7 in (1.78 cm)

Process Connection 1 QTHA-2MB0

Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Country of origin	USA
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa

Process Connection 1 QTHA-2MB0

Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	1.09 oz / 31 grams
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)

Process Connection 2 QTHA-2MB0

Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Country of origin	USA
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	1.09 oz / 31 grams
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)

Hose 1 QTQT-HOS-2m

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	2 m / 6.56 ft
Inner Diameter	0.08 In / 3.00 mm
Length	2.00 m / 6 ft 7 in
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water

Hose 1 QTQT-HOS-2m

Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	3.28 oz / 93 grams

Hose 2 QTQT-HOS-1m

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	1 m / 3.28 ft
Inner Diameter	0.08 In / 3.00 mm
Length	1.00 m / 3 ft 3 in
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	2.67 oz / 76 grams