

Part No.

# SPOV-1MSA-6-3

*Gas Sampling Pump, 2 hoses, 1/4" Male NPT gauge connection*

The SPOV gas sampling pump can pull low pressure gas from a well and boost it to 25 psi to pump it into a sample cylinder



SPOV-1MSA-6-3

## Included Items

- Hose 2 - Quick-test 6900 psi hose, S.S. hose ends, 3 ft (92 cm) long (QSQS-HOS-3ft)
- Hose 1 - Quick-test 6900 psi hose, S.S. hose ends, 6 ft (1.83 m) long (QSQS-HOS-6ft)
- Gauge Swivel - 1/8" male NPT x female Quick-test, no check-valve, S.S. (QTHA-1MSA)
- Adapter 1 - QTHA-2MS0-VT (QTHA-2MS0-VT)
- Hand Pump - SPOV Assembly (SPOV)

## Specs/Attributes

Burst Pressure	27000 PSI
Color	Silver
Fine Adjustment Resolution	.01 PSI
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Has Check Valve	No
Hose 1	Quick-test Hose, Stainless Steel ends, 2ft / 0.6m long
Inlet Port	Male Quick-test with check-valve
Inner Diameter	0.08 In
Length	3, 6 ft
Materials	Anodized Aluminum, Stainless Steel
Max Pressure	100 PSI
Max Temperature	130 °F
Max Vacuum	In Hg
Media Compatibility	Air, Inert Gas, Natural Gas
Min Temperature	-40 °F

## Specs/Attributes

Minimum Bend Radius	1 In
Outer Diameter	0.2 In
Outlet Port	Male Quick-test, Male Quick-test with cap and chain
Pressure Reference	None
Process Connection	1/4
Reference Connection	1/2
Seal Materials	Viton
Type	QT
Wrench Size	9/16 In 15 mm