

Part No.

SPOV-1MSA-6-3

Gas Sampling Pump, 2 hoses, 1/4" Male NPT gauge connection

The SPOV gas sampling pump can pull low pressure gas from a well and boost it to 25 psi to pump it into a sample cylinder



SPOV-1MSA-6-3

Included Items

- Hose 2 - Quick-test 6900 psi hose, S.S. hose ends, 3 ft (92 cm) long (QSQS-HOS-3ft)
- Hose 1 - Quick-test 6900 psi hose, S.S. hose ends, 6 ft (1.83 m) long (QSQS-HOS-6ft)
- Gauge Swivel - 1/8" male NPT x female Quick-test, no check-valve, S.S. (QTHA-1MSA)
- Adapter 1 - QTHA-2MS0-VT (QTHA-2MS0-VT)
- Hand Pump - SPOV Assembly (SPOV)

Specs/Attributes

Materials	Anodized Aluminum, Stainless Steel
Seal Materials	Viton
Max Pressure	100 PSI / 7 bar / 700 kPa
Max Temperature	130 °F / 54 °C
Hose 1	Quick-test Hose, Stainless Steel ends, 2ft / 0.6m long
Pressure Reference	None
Process Connection	1/4
Reference Connection	1/2
Weight	27.04 oz / 765 grams
Dimensions	H: 4.75 in (12.07 cm) x W: 3.75 in (9.53 cm) x D: 7.75 in (19.69 cm)

Hose 2 QSQS-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Inner Diameter	0.08 In / 3.00 mm

Hose 2 QSQS-HOS-3ft

Length	3 ft / 92 cm
Materials	Stainless Steel
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Temperature	140 °F / 60 °C
Max Vacuum	0.00 In Hg / 0.00 mm Hg
Min Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT

Hose 1 QSQS-HOS-6ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Inner Diameter	0.08 In / 3.00 mm
Length	6 ft / 2.00 m
Materials	Stainless Steel
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Temperature	140 °F / 60 °C
Max Vacuum	0.00 In Hg / 0.00 mm Hg
Min Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT

Gauge Swivel QTHA-1MSA

Has Check Valve	No
Materials	Stainless Steel
Max Pressure	5000 PSI / 345 bar / 35 MPa
Max Temperature	225 °F / 105 °C
Max Vacuum	0.00 In Hg / 0.00 mm Hg
Wrench Size	9/16 In 15 mm
Dimensions	H: 1.55 in (3.94 cm) x W: 0.7 in (1.78 cm)

Adapter 1 QTHA-2MS0-VT

Materials	Stainless Steel
Seal Materials	Viton

Hand Pump SP0V

Max Pressure	100 PSI / 7 bar / 700 kPa
Max Temperature	130 °F / 54 °C

Hand Pump SP0V

Fine Adjustment Resolution	0 PSI / 0 mbar / 0.00 kPa
Materials	Anodized Aluminum, Stainless Steel
Media Compatibility	Air, Inert Gas, Natural Gas
Min Temperature	0 °F / -18 °C
Outlet Port	Male Quick-test, Male Quick-test with cap and chain
Seal Materials	Delrin, Viton
Inlet Port	Male Quick-test with check-valve
Weight	25.6 oz / 725 grams
Dimensions	H: 2.9 in (7.37 cm) x W: 8 in (20.32 cm) x D: 3.4 in (8.64 cm)