

Part No.

XREG-KIT4

3000 PSI Regulator, 2 pressure gauges, BS 341 type 3 inlet connection, Male Quick-test outlet conn. kit

Piston sensed pressure reducing regulator for use in providing a stable pressure to precision pressure control devices.



XREG-KIT4

Included Items

- Regulator - XREG Pressure Regulator (XREG)
- Adapter 1 - Cylinder adapter, BS341 TYPE 3 - Quick-connect x 1/4" Male NPT adapter, S.S. (QTHA-2MS0-B341T03-QD)
- Adapter 2 - 1/4" male NPT x male Quick-test, no check-valve, S.S. (QTHA-2MS0)
- Pressure Gauge (Qty 2) - 2.5" 3000 PSI / 200 bar gauge, 1/4" MNPT lower mount (ST-0026)

Specs/Attributes

Max Pressure	3000 PSI / 200 bar / 20 MPa
Materials	Anodized Aluminum, Stainless Steel
Seal Materials	Buna-N, Delrin, Teflon, Urethane
Country of origin	USA
Max Operating Temperature	130 °F / 54 °C
Media Compatibility	Air, Inert Gas
Min Operating Temperature	0 °F / -18 °C
Weight	2.44 lbs / 1.11 kg
Dimensions	H: 7.75 in (19.69 cm) x W: 7.75 in (19.69 cm) x D: 7.75 in (19.69 cm)

Regulator XREG

Harmonized Code	8481.10.0040
Max Pressure	3000 PSI / 200 bar / 20 MPa

Regulator XREG

Materials	Anodized Aluminum, Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Media Compatibility	Air, Inert Gas
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Delrin, Teflon
Country of origin	USA

Adapter 1 QTHA-2MS0-B341T03-QD

Certifications	BS 341 Type 3 (United Kingdom)
Country of origin	USA
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Urethane
Connector End 1	Type 3 Male BS 341
Connector End 2	1/4" Male NPT (ASME B1.20.1)
Weight	11.18 oz / 315 grams
Dimensions	H: 4.25 in (10.8 cm) x W: 1.45 in (3.68 cm) x D: 1.45 in (3.68 cm)

Adapter 2 QTHA-2MS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test

Adapter 2 QTHA-2MS0

Weight	1.01 oz / 29 grams
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)

Pressure Gauge (Qty 2) ST-0026

Accuracy - Pressure Measurement	+/- 3/2/3% of Full Scale (ASME B40.100 Grade B)
Country of origin	USA
Measurement Type	Gauge Pressure
Process Connection	1/4" Male NPT (ASME B1.20.1)