

Part No.

XTHP-EP-0000

10kpsi / 70 MPa Hydraulic hand pump with EPDM seals, 2 Quick-test XT outlet ports, 3 ft hose, 1/4" MNPT Process conn.

10kpsi / 70 MPa Hydraulic hand pump, 2 Quick-test XT outlet ports, 3 ft hose, 1/4" MNPT Process conn.



XTHP-EP-0000

Included Items

- Hand Pump - XTHP Hydraulic Pump with EPDM seals (XTHP-EP)
- Hose - Quick-test XT 10,000 psi hose, S.S. hose ends, 3ft long (XTXT-HOS-3ft)
- Process Connection - 1/4" male NPT x male Quick-test XT Adapter, EPDM seals, S.S. (XTHA-2MS0-EP)
- Bottle - Bottle with flip top for Hydraulic pump fluid, empty (QTHP-BOTL)

Specs/Attributes

Country of origin	USA
Weight	3.25 lbs / 1.47 kg
Dimensions	H: 5.7 in (14.48 cm) x W: 7.5 in (19.05 cm) x D: 10.6 in (26.92 cm)

Hand Pump XTHP-EP

Materials	Anodized Aluminum, Delrin, Polysulfone, Stainless Steel
Max Pressure	10000 PSI / 700 bar / 70 MPa
Media Compatibility	Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Light motor oil, Mineral Oil, Petroleum Based Oil, Ralston Calibration Oil, Skydrol, Transmission fluid, Windshield washer fluid
Seal Materials	Teflon, EPDM

Hand Pump XTHP-EP

Outlet Port	Male Quick-test XT, Male Quick-test XT with cap and chain
Pressure Media	Liquid
Burst Pressure	40000 PSI / 2760 bar / 275 MPa
Reservoir Volume	4.2 fl. oz
Max Operating Temperature	140 °F / 60 °C
Harmonized Code	8413.20.0000
Country of origin	USA
Min Operating Temperature	-15 °F / -26 °C
Fine Adjustment Resolution	0.01 psi / 70 Pa
Weight	3.12 lbs / 1.41 kg
Dimensions	H: 5.7 in (14.48 cm) x W: 7.5 in (19.05 cm) x D: 10.6 in (26.92 cm)

Hose XTXT-HOS-3ft

Burst Pressure	40000 PSI / 2760 bar / 275 MPa
Color	Blue
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Inner Diameter	0.08 In / 3.00 mm
Length	3 ft / 92 cm
Materials	Reinforced Polyamide, Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	10000 PSI / 700 bar / 70 MPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.24 In / 7.00 mm
Type	XT
Weight	2.94 oz / 83 grams

Process Connection XTHA-2MS0-EP

Country of origin	USA
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	10000 PSI / 700 bar / 70 MPa

Process Connection XTHA-2MS0-EP

Min Operating Temperature	0 °F / -18 °C
Seal Materials	Teflon, EPDM
Wrench Size	5/8 In 16 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test XT
Dimensions	H: 1.29 in (3.28 cm) x W: 0.71 in (1.8 cm) x D: 0.71 in (1.8 cm)

Bottle QTHP-BOTL

Materials	Nylon
Country of origin	USA
Weight	1.26 oz / 36 grams
Dimensions	H: 7.25 in (18.42 cm) x W: 2.32 in (5.89 cm) x D: 2.32 in (5.89 cm)